

# C2ENET-1

## Single Port Ethernet Card for Z-Bus Expansion Slot

The C2ENET-1 is a 10/100BaseT half/full duplex Ethernet card that installs in any Z-Bus expansion slot of a 2-Series control system. The C2ENET-1 provides Ethernet connectivity to enable the control system's built-in Web server and e-Control@2 capabilities. The C2ENET-1 allows remote diagnostics and programming as well as Ethernet intersystem communications (EIC) over an Ethernet LAN, WAN or Internet.

### SPECIFICATIONS

#### Connectors

---

LAN A: (1) 8-wire RJ45 with 2 LED indicators;  
10/100BaseT Ethernet port;  
Green LED indicates link status;

#### Power Requirements

---

Cresnet Power Usage: 2 Watts (0.083 Amps @ 24 Volts DC)

#### Environmental

---

Temperature: 41° to 113°F (5° to 45°C)  
Humidity: 10% to 90% RH (non-condensing)

#### Construction

---

Z-bus expansion card, occupies (1) Z-bus card slot in a 2-Series control system

#### Dimensions

---

Height: 0.98 in (2.49 cm)  
Width: 4.28 in (10.86 cm)  
Depth: 4.71 in (11.95 cm)

# C2ENET-1

## Single Port Ethernet Card for Z-Bus Expansion Slot

